

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>C10L 1/18</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 98/01516</b> <b>(43) International Publication Date:</b> 15 January 1998 (15.01.98)
<b>(21) International Application Number:</b> PCT/EP97/03591 <b>(22) International Filing Date:</b> 4 July 1997 (04.07.97) <b>(30) Priority Data:</b> 96304975.4 5 July 1996 (05.07.96) EP <b>(34) Countries for which the regional or international application was filed:</b> GB et al. <b>(71) Applicant:</b> SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL). <b>(72) Inventors:</b> LIN, Jian; Pool Lane, Ince, Chester, Cheshire CH1 3SH (GB). ROBERTSON, Struan, Douglas; Pool Lane, Ince, Chester, Cheshire CH1 3SH (GB).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> FUEL OIL COMPOSITIONS  <b>(57) Abstract</b>  This invention provides a fuel oil composition comprising a major amount of a fuel oil and a minor amount of an additive comprising at least one fuel oil-soluble alkyl or alkoxy aromatic compound wherein at least one group independently selected from alkyl and alkoxy groups of 1 to 30 carbon atoms is attached to an aromatic nucleus and at least one carboxyl group and optionally one or two hydroxyl groups are attached to the aromatic nucleus; a process for the preparation of such a fuel oil composition; and the use of such a fuel oil composition as fuel in a compression-ignition engine for controlling wear rate in the fuel injection system thereof.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

- 1 -

## FUEL OIL COMPOSITIONS

This invention relates to fuel oil compositions, processes for their preparation, and their use in compression-ignition engines.

As stated in WO 9533805 (Exxon) environmental concerns have led to a need for fuels with reduced sulphur content, especially diesel fuel and kerosene. However, the refining processes that produce fuels with low sulphur contents also result in a product of lower viscosity and a lower content of other components in the fuel that contribute to its lubricity, for example, polycyclic aromatics and polar compounds. Furthermore, sulphur-containing compounds in general are regarded as providing anti-wear properties and a result of the reduction in their proportions, together with the reduction in proportions of other components providing lubricity, has been an increase in reported failures of fuel pumps in diesel engines using low-sulphur fuels, the failure being caused by wear in, for example, cam plates, rollers, spindles and drive shafts.

This problem may be expected to become worse in future because, in order to meet stricter requirements on exhaust emissions generally, high pressure fuel pumps, for example rotary and unit injector systems, are being introduced, these being expected to have more stringent lubricity requirements than present equipment, at the same time as lower sulphur levels in fuels become more widely required.

At present, a typical sulphur content in a diesel fuel is about 0.25% by weight (2500 ppmw). In Europe maximum sulphur levels have been reduced to 0.05% (500 ppmw); in Sweden grades of fuel with levels below 0.005% (50 ppmw) (Class 2) and 0.001% (10 ppmw) (Class

- 2 -

1) are already being introduced. Fuel oils with a sulphur level below 0.20% by weight (2000 ppmw) may be referred to as low-sulphur fuels.

5 WO 95 33805 (Exxon) describes the use of cold flow improvers to enhance lubricity of low-sulphur fuels.

WO 94 17160 (Exxon) describes the use of certain esters of a carboxylic acid and an alcohol wherein the acid has from 2 to 50 carbon atoms and the alcohol has one or more carbon atoms, particularly glycerol  
10 monooleate and di-isodecyl adipate, as additives for fuel oils for wear reduction in the injection system of a compression-ignition engine.

US Patent 5,484,462 (Texaco) mentions dimerized linoleic acid as a commercially available lubricity  
15 agent for low sulphur diesel fuel (Col. 1, line 38), and itself provides aminoalkylmorpholines as fuel lubricity improvers.

US Patent 5,490,864 (Texaco) describes certain dithiophosphoric diester-dialcohols as anti-wear  
20 lubricity additives for low-sulphur diesel fuels.

It has now surprisingly been found that certain alkyl and alkoxy aromatic compounds having at least one carboxyl group attached to their aromatic nuclei can confer anti-wear lubricity effects when incorporated in  
25 fuel oil.

According to the present invention therefore there is provided a fuel oil composition comprising a major amount of a fuel oil and a minor amount of an additive comprising at least one fuel oil-soluble alkyl or  
30 alkoxy aromatic compound wherein at least one group independently selected from alkyl and alkoxy groups of 1 to 30 carbon atoms is attached to an aromatic nucleus and at least one carboxyl group and optionally one or two hydroxyl groups are attached to the aromatic  
35 nucleus.

- 3 -

The fuel oil may be derived from petroleum or from vegetal sources or a mixture thereof. It may conveniently be a middle distillate fuel oil having a boiling range in the range 100°C to 500°C, e.g. 150°C to 400°C. Petroleum-derived fuel oils may comprise atmospheric distillate or vacuum distillate, or cracked gas oil or a blend in any proportion of straight run and thermally and/or catalytically cracked distillates. Fuel oils include kerosine, jet fuels, diesel fuels, heating oils and heavy fuel oils. Preferably the fuel oil is a diesel oil, and preferred fuel oil compositions of the invention are thus diesel fuel compositions. Diesel fuels typically have initial distillation temperature about 160°C and final distillation temperature of 290-360°C, depending on fuel grade and use.

A fuel oil, e.g. diesel oil, itself may be an additised (additive-containing) oil or an unadditised (additive-free) oil. If the fuel oil, e.g. diesel oil, is an additised oil, it will contain minor amounts of one or more additives, e.g. one or more additives selected from anti-static agents, pipeline drag reducers, flow improvers (e.g. ethylene/vinyl acetate copolymers or acrylate/maleic anhydride copolymers) and wax anti-settling agents (e.g. those commercially available under the Trade Marks "PARAFLOW" (e.g. "PARAFLOW" 450; ex Paramins), "OCTEL" (e.g. "OCTEL" W 5000; ex Octel) and "DODIFLOW" (e.g. DODIFLOW" v 3958; ex Hoechst).

Preferably the fuel oil is a middle distillate oil, e.g. a diesel oil, having a sulphur content of at most 0.2 % by weight (2000 ppmw) ("ppmw" is parts per million by weight), more preferably at most 0.05% by weight (500 ppmw). Advantageous compositions of the invention are also attained when the sulphur content of

- 4 -

the fuel oil is below 0.005 % by weight (50 ppmw) or even below 0.001% by weight (10 ppmw).

Although the aromatic nucleus of the alkyl or alkoxy aromatic compound may be monocyclic, bicyclic or polycyclic, e.g. a benzene ring or a naphthalene ring system, the aromatic nucleus is preferably a benzene ring.

Preferred alkyl and alkoxy aromatic compounds are those in which whenever there are less than three groups selected from alkyl and alkoxy groups attached to the aromatic nucleus, there is at least one group selected from alkyl and alkoxy groups of 2 to 30 carbon atoms attached to said nucleus.

In one preferred aspect of the present invention, the at least one alkyl or alkoxy aromatic compound is an alkyl aromatic compound wherein at least one alkyl group of 6 to 30 carbon atoms is attached to the aromatic nucleus.

More preferably, the alkyl aromatic compound is an alkyl benzoic acid or an alkyl salicylic acid containing one or two alkyl groups of 6 to 30 carbon atoms.

The or each alkyl group in the alkyl aromatic compound is preferably a C<sub>8</sub>-22 alkyl group, most preferably a C<sub>8</sub>-18 alkyl group.

The alkyl or alkoxy aromatic compounds incorporated in fuel oil compositions of the present invention are either known compounds or can be prepared by methods analogous to methods used for preparing known compounds, as will readily be appreciated by those skilled in the art.

Preferred alkyl salicylic acids may be very readily be prepared by the methods described in UK Patent 1,146,925. (In that patent, the alkyl salicylic acids are intermediates in the preparation of polyvalent

- 5 -

metal salts used as dispersants in lubricant compositions).

5 The additive comprising the at least one alkyl or alkoxy aromatic compound is preferably present in an amount in the range 50 to 500 ppmw, more preferably 50 to 250 ppmw, most preferably 150 to 250 ppmw, based on the total weight of the fuel composition.

10 Alkyl or alkoxy aromatic compounds which will not dissolve in fuel oil at ambient temperature to an extent of 50 ppmw are not fuel-oil soluble as defined herein (they are thus considered to be insoluble)

15 Fuel oil compositions in accordance with the invention may be prepared by a process for their preparation which comprises admixing the additive or an additive concentrate containing the additive with the fuel oil.

20 Additive concentrates suitable for incorporating in the fuel oil compositions (preferably diesel fuel compositions) will contain the additive comprising the at least one alkyl or alkoxy aromatic compound and a fuel-compatible diluent, which may be a carrier oil (e.g. a mineral oil), a polyether, which may be capped or uncapped, a non-polar solvent such as toluene, xylene, white spirits and those sold by member  
25 companies of the Royal Dutch/Shell Group under the Trade Mark "SHELLSOL", and/or a polar solvent such as esters and, in particular, alcohols, e.g. hexanol, 2-ethylhexanol, decanol, isotridecanol and alcohol mixtures such as those sold by member companies of the  
30 Royal Dutch/Shell Group under the Trade Mark "LINEVOL", especially "LINEVOL" 79 alcohol which is a mixture of C<sub>7-9</sub> primary alcohols, or the C<sub>12-14</sub> alcohol mixture commercially available from Sidobre Sinnova, France under the Trade Mark "SIPOL".

- 6 -

Additive concentrates and fuel oil compositions prepared therefrom may further contain additional additives such as ashless detergents or dispersants, e.g. linear or branched hydrocarbyl amines, for example alkylamines, hydrocarbyl-substituted succinimides, such as those described in EP-A-147 240, preferably the reaction product of a polyisobutylene succinic acid or anhydride with tetraethylene pentamine wherein the polyisobutylene substituent has a number average molecular weight (Mn) in the range 500 to 1200, and/or an alkoxy acetic acid derivative as described in European Patent Application No. 96302953.3 (Applicant's reference TS 7030 EPC); dehazers, e.g. alkoxyated phenol formaldehyde polymers such as those commercially available as "NALCO" (Trade Mark) EC5462A (formerly 7D07) (ex Nalco), and "TOLAD" (Trade Mark) 2683 (ex Petrolite); anti-foaming agents (e.g. the polyether-modified polysiloxanes commercially available as "TEGOPREN" (Trade Mark) 5851, Q 25907 (ex Dow Corning) or "RHODORSIL" (ex Rhone Poulenc)); ignition improvers (e.g. 2-ethylhexyl nitrate, cyclohexyl nitrate, di-tertiarybutyl peroxide and those disclosed in US Patent No. 4,208,190 at Column 2, line 27 to Column 3, line 21); anti-rust agents (e.g. that commercially sold by Rhein Chemie, Mannheim, Germany as "RC 4801", or polyhydric alcohol esters of a succinic acid derivative, the succinic acid derivative having on at least one of its alpha-carbon atoms an unsubstituted or substituted aliphatic hydrocarbon group containing from 20 to 500 carbon atoms, e.g. the pentaerythritol diester of polyisobutylene-substituted succinic acid), reodorants, anti-wear additives; anti-oxidants (e.g. phenolics such as 2,6-di-tert-butylphenol, or phenylenediamines such as N,N'-di-sec-butyl-p-phenylenediamine); and metal deactivators.



- 7 -

Unless otherwise stated, the (active matter) concentration of each additional additive in the diesel fuel is preferably up to 1 percent by weight, more preferably in the range from 5 to 1000 ppmw (parts per million by weight of the diesel fuel). The (active matter) concentration of the detergent or dispersant in the diesel fuel is preferably 30 to 1000 ppmw, more preferably 50 to 600 ppmw, advantageously 75 to 300 ppmw e.g. 95 to 150 ppmw.

The (active matter) concentration of the dehazer in the diesel fuel is preferably in the range from 1 to 20 ppmw, more preferably from 1 to 15 ppmw, still more preferably from 1 to 10 ppmw and advantageously from 1 to 5 ppmw. The (active matter) concentrations of other additives (with the exception of the ignition improver are each preferably in the range from 0 to 20 ppmw, more preferably from 0 to 10 ppmw. The (active matter) concentration of the ignition improver in the diesel fuel is preferably in the range from 0 to 600 ppmw and more preferably from 0 to 500 ppmw. If an ignition improver is incorporated into the diesel fuel, it may conveniently be used in an amount of 300 to 500 ppmw.

The invention further provides the use of a fuel composition as defined above as fuel in a compression-ignition engine for controlling wear rate in the fuel injection system of the engine, especially in fuel injection pumps and/or fuel injectors.

This latter aspect of the invention may also be expressed as a method of operating a compression-ignition engine which comprises providing a fuel composition as defined above as the fuel in the engine thereby to control wear rate in the fuel injection system of the engine, especially the fuel injection pump and/or fuel injectors.

- 8 -

The invention will be further understood from the following illustrative examples, in which the base fuels and additive components were as follows:-

	<u>Base Fuel 1</u>	<u>Base Fuel 2</u>	<u>Base Fuel 3</u>	<u>Fuel Fuel 4</u>
Density (kg/l) at 15°C (ASTM D 4052)	0.821	0.8291	0.8165	0.8165
Sulphur (ppmw) (IP 373)	182	145	2	<5
Distillation, degrees C (ASTM D 86)				
IBP	166.5	167	184.5	184.5
10%	203.5	199	213	206.5
20%	216	210.5	218.5	213.5
50%	256.5	247.5	238	235.5
90%	322.5	309.5	269.5	268.5
95%	342.5	324.5	278.5	277.5
FBP	355	338.5	292	290
Total Aromatics content (%w)	20.2	22.1	5.2	3.8

5     "Alkylsalicylic acid A" was prepared from C<sub>14-18</sub>  
 alkyphenol by phenation, carboxylation and hydrolysis,  
 as described in UK Patent 1,146,925. The starting  
 alkyphenol was prepared from a mixture of olefins  
 (C<sub>14</sub>:C<sub>16</sub>:C<sub>18</sub> weight ratio 1:2:1), by reacting phenol  
 10     and the olefins (molar ratio 5:1) in the presence of  
 3%w, based on the olefins, of acid-activated  
 montmorillonite catalyst at 190°C and 0.4 bar  
 (4 x 10<sup>4</sup> Pa) pressure, with excess phenol being removed  
 by distillation. The end-product C<sub>14-18</sub> alkylsalicylic  
 acid contained 71.5% mol monoalkylsalicylic acid,  
 15     17.2% mol monoalkyl phenol, and 4.7% mol dialkylphenol,  
 the balance being minor quantities of 4-hydroxyiso-  
 phthalic acid, dialkyl salicylic acid, 2-hydroxyiso-  
 phthalic acid and alkyl phenyl ether.

- 9 -

"Carrier B" is a polyoxypropylene glycol hemiether (monoether) prepared using a mixture of C<sub>12-15</sub> alcohols as initiator, and having M<sub>n</sub> in the range 1200 to 1500 and a kinematic viscosity in the range 72 to 82 mm<sup>2</sup>/s at 40°C according to ASTM D 445, available under the trade designation "SAP 949" from member companies of the Royal Dutch/Shell group.

"Oil C" is a clear and bright solvent refined base oil having viscosity at 100°C of 4.4 to 4.9 mm<sup>2</sup>/s, pour point -18°C, and flash point 204°C, available under the trade designation "HVI 60" from member companies of the Royal Dutch/Shell group.

"Anti-Rust Agent D" is a hydroxypropyl ester of tetrapropenyl succinic acid (propane-1,2-diol semi-ester of tetrapropenyl succinic acid) (c.f. Example IV of UK Patent 1,306,233).

Dehazer E" is an alkoxyated phenol formaldehyde polymer dehazer available ex Nalco as "NALCO" EC5462A (formerly 7D07) (trade mark).

"Antifoaming Agent F" is a polyether-modified siloxane available ex Th. Goldschmidt AG as "TEGOPREN 5851" (trade mark).

"Solvent G" is a blend of C<sub>7-9</sub> primary alcohols available from member companies of the Royal Dutch/Shell group as "LINEVOL 79" (trade marks).

"Solvent H" is an aromatic hydrocarbon solvent (74% aromatic) of boiling range 205 to 207°C and average molecular weight 156, available from member companies of the Royal Dutch/Shell group as "SHELLSOL R" (trade mark).

"Dispersant I" is a 27% w solution of polyisobutylene succinimide prepared by reaction of a polyisobutylene of number average molecular weight (M<sub>n</sub>) 950 with maleic

- 10 -

anhydride, to yield a polyisobutylene succinic anhydride product having a succination ratio (ratio of succinic anhydride moieties per polyisobutylene chain) 1.05:1, followed by reaction of the anhydride product with tetraethylene pentamine (TEPA) in molar ratio succinic groups: TEPA 1.5:1. A solution of the polyisobutylene succinimide containing 47% w active ingredient in "HVI 60" base oil is diluted to the active ingredient concentration of 27% w by addition of "SHELLSOL R" (trade mark) solvent, for ease of handling.

#### EXAMPLE I

An additive concentrate was prepared by mixing 69 g of a solution of alkylsalicylic acid A (45 g) in xylene (24 g), 16 g of Oil C and 15 g of Carrier B, in a sealed 250 ml glass bottle for 1 hour on a rotary mixer at ambient temperature (20°C) to give 100 g of well mixed additive concentrate I.

#### EXAMPLE II

A co-additive mixture was prepared by mixing together 0.3319 g of Anti-Rust Agent D, 0.3325 g of Dehazer E, 0.6791 g of Antifoaming Agent F, 6.6739 g of Solvent G, 12.8809 g of Solvent H, 32.44 g of Dispersant I and 33.66 g of 2-ethylhexylnitrate (ignition improver).

1.0498 g of the resulting co-additive mixture was then mixed in a 250 ml glass beaker with 0.1620 g of the additive concentrate I of Example I to yield additive concentrate II.

When additive concentrate II was used to prepare a formulated diesel fuel, 50 ml of Base Fuel 1 was added to the above sample of additive concentrate II and the resulting mixture was stirred thoroughly before being poured into a 1 litre lacquer-lined can. The glass beaker was then rinsed with another 50 ml portion of

- 11 -

Base Fuel 1 into the same can. Total weight of formulated fuel was made up to 801 g by addition of Base Fuel 1. The can was shaken for 2 minutes to yield a homogeneous formulated diesel fuel containing 1500 ppmw of additive concentrate II.

#### EXAMPLE III

An additive concentrate was prepared by mixing 45 g of Alkylsalicylic acid A with 24 g of Solvent H, 16 g of Oil C and 15 g of Carrier B, by a procedure similar to that of Example I to yield additive concentrate III.

#### EXAMPLE IV

An additive concentrate was prepared similarly to Example III by mixing 45 g of Alkylsalicylic acid A with 39 g of Solvent A and 16 g of Oil C to yield additive concentrate IV.

#### FUEL TEST EXAMPLES

Formulated diesel fuels were prepared by adding quantities of the additive concentrates I, III and IV to various of the Base Fuels 1, 2 and 3. The resulting fuels were tested for lubricity performance by the High Frequency Reciprocating Rig (HFRR) test, according to the procedure of CEC F-06-T-94 with the exception that the value of fuel used was 2 ml and the fluid temperature was 60°C.

Details of the formulated diesel fuels tested, and results of the tests, are given in Table 1 following:

Table 1

Fuel Example	Base Fuel	Additive Concentrate (AC)	Concentration of AC in Fuel (ppmw)	Concentration of Alkyl salicylic Acid A in Fuel (ppmw)	Average wear scar diameter (microns, $m \times 10^{-6}$ )
Comparative A	1	-	-	-	597
1	1	I	110	50	472
2	1	I	170	75	429
3	1	I	225	100	415
4	1	I	335	150	396
5	1	I	445	200	398
6	1	II	1500	90	483
7	1	IV	225	100	378
Comparative B	2	-	-	-	610
8	2	III	110	50	518
9	2	III	170	75	461
10	2	III	225	100	440
11	2	III	335	150	390
12	2	IV	225	100	434

Table 1 (continued)

Fuel Example	Base Fuel	Additive Concentrate (AC)	Concentration of AC in Fuel (ppmw)	Concentration of Alkyl salicylic Acid A in Fuel (ppmw)	Average wear scar diameter (microns, $m \times 10^{-6}$ )
Comparative C	3	-	-	-	660
13	3	III	170	75	539
14	3	III	340	150	391
15	3	III	510	230	383

- 14 -

It can readily be seen from the results in Table 1 that even at low treat rates surprisingly enhanced lubricity, as evidenced by wear reduction, is attained even at low concentrations of Alkylsalicylic Acid A.

5     FURTHER FUEL TEST EXAMPLES

Further diesel fuels were prepared by adding quantities of a number of different alkyl aromatic compounds to Base Fuel 1 to concentrations of 100 ppmw. The resulting fuels were tested for lubricity  
10     performance as described in the fuel test examples above, except that a different, although similar pattern, rig was used (this accounts for the small, and insignificant, difference in wear scar for the base fuel test Comparative D relative to that of Comparative  
15     A above).

The alkyl aromatic compounds used were as follows:-

- Example 16     - 4-octylbenzoic acid
- Example 17     - 4-n-butylbenzoic acid
- Example 18     - 4-dodecyloxybenzoic acid
- 20     Comparative E   - 3-pentadecyl phenol
- Comparative F   - dodecylphenol, available ex Adibis  
                    under the trade designation "ADX 100".
- Comparative G   - C<sub>14-18</sub> alkylphenol, the starting  
                    alkylphenol of alkylsalicylic acid A  
25                      described above.

Results are given in Table 2 following:



- 15 -

Table 2

Fuel Example	Average wear scar diameter (microns, $m \times 10^{-6}$ )
Comparative D (no additive)	565
Example 16	308
Example 17	250
Example 18	319
Comparative E	562
Comparative F	559
Comparative G	559

5 Directly equivalent tests to those of Table 2 were done using base fuel 4 (Comparative H) and 200 ppmw concentrations of 2,4,6-trimethylbenzoic acid (Example 19) and 4-ethylbenzoic acid (Example 20). Results are given in Table 3 following:

Table 3

Fuel Example	Average wear scar diameter (microns, $m \times 10^{-6}$ )
Comparative H (no additive)	622
Example 19	387
Example 20	352

10 It can readily be seen from Tables 2 and 3 that surprisingly enhanced lubricity was obtained for the fuel containing the alkyl or alkoxybenzoic acids (4-octylbenzoic acid, 4-n-butylbenzoic acid 4-dodecyloxybenzoic acid, 2,4,6-trimethylbenzoic acid and 15 4-ethylbenzoic acid), whereas no positive effect was found in the case of any of the alkylphenols.

2,3-Dimethylbenzoic acid, 2,4-dimethylbenzoic acid and 3,4-dimethylbenzoic acid were each tested for

- 16 -

solubility at a concentration of 50 ppmw in fuel oil, specifically Base Fuel 4, and were found to be insoluble at ambient temperature (20°C). These dimethylbenzoic acids are thus not fuel oil-soluble alkyl aromatic compounds.

5

- 17 -

C L A I M S

1. A fuel oil composition comprising a major amount of a fuel oil and a minor amount of an additive comprising at least one fuel oil-soluble alkyl or alkoxy aromatic compound wherein at least one group independently  
5 selected from alkyl and alkoxy groups of 1 to 30 carbon atoms is attached to an aromatic nucleus and at least one carboxyl group and optionally one or two hydroxyl groups are attached to the aromatic nucleus.
2. A composition according to Claim 1 wherein the fuel  
10 oil is a middle distillate fuel oil having a sulphur content of at most 0.05% by weight.
3. A composition according to Claim 1 or 2 wherein whenever there are less than these groups selected from alkyl and alkoxy groups attached to the aromatic  
15 nucleus, there is at least one group selected from alkyl and alkoxy groups of 2 to 30 carbon atoms attached to said nucleus.
4. A composition according to any one of Claims 1 to 3 wherein the at least one alkyl or alkoxy aromatic  
20 compound is an alkyl aromatic compound wherein at least one alkyl group of 6 to 30 carbon atoms is attached to the aromatic nucleus.
5. A composition according to any one of Claims 1 to 4 wherein in the alkyl or alkoxy aromatic compound the  
25 aromatic nucleus is a benzene ring.
6. A composition according to Claim 5 wherein the alkyl aromatic compound is an alkyl benzoic acid or an alkyl salicylic acid containing one or two alkyl groups of 6 to 30 carbon atoms.
7. A composition according to any one of Claims 1 to 6  
30 wherein the or each alkyl group is a C<sub>8-22</sub> alkyl group.

- 18 -

8. A composition according to any one of Claims 1 to 7 wherein the additive is present in an amount in the range 50 to 500 ppmw based on the total weight of the fuel composition.
- 5 9. A process for the preparation of a fuel oil composition according to any one of Claims 1 to 8 which comprises admixing the additive or an additive concentrate containing the additive with the fuel oil.
- 10 10. Use of a fuel oil composition according to any one of Claims 1 to 8 as fuel in a compression-ignition engine for controlling wear rate in the fuel injection system of the engine.

## INTERNATIONAL SEARCH REPORT

Internat. Application No

PCT/EP 97/03591

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 C10L1/18

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C10L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 482 521 A (AVERY ET AL.) 9 January 1996 see abstract see column 7, line 12 - line 50 see column 10, line 21 - line 23 ---	1-3,5, 8-10
X	GB 1 324 162 A (SHELL) 18 July 1973 see the whole document ---	1,3-9
X	DE 15 45 507 A (SHELL) 27 November 1969  see claims 48,49 ---	1,3-5, 7-9
X	FR 1 232 157 A (SHELL) 5 October 1960 see the whole document ---	1,5,9
	--- -/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*Z\* document member of the same patent family

Date of the actual completion of the international search

17 October 1997

Date of mailing of the international search report

30.10.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

De La Morinerie, B

## INTERNATIONAL SEARCH REPORT

International Application No  
PCT/EP 97/03591

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 911 491 A (ETHYL) 28 November 1962 see page 2, line 56 ---	1,3,5,8, 9
X	US 3 541 723 A (ECKERT) 24 November 1970 see column 3, line 24 ---	1,3,5,8, 9
X	DE 17 45 911 A (BASIC INC.) 14 January 1971 see claim 3 ---	1,5,8,9
X	US 5 522 906 A (HASHIMOTO ET AL.) 4 June 1996 see column 6, line 48 ---	1,3,5,8, 9
X	US 4 828 733 A (FARNG ET AL.) 9 May 1989 see the whole document -----	1,3-5, 7-9

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Internatic Application No

PCT/EP 97/03591

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5482521 A	09-01-96	US 5538653 A US 5601699 A	23-07-96 11-02-97
GB 1324162 A	18-07-73	DE 2044480 A FR 2061100 A NL 7013231 A SE 367817 B US 3730485 A	11-03-71 18-06-71 12-03-71 10-06-74 01-05-73
DE 1545507 A	27-11-69	BE 688966 A CH 488002 A FR 1499552 A GB 1124611 A NL 6615175 A SE 325441 B	27-04-67 31-03-70   02-05-67 29-06-70
FR 1232157 A	05-10-60	BE 581520 A CH 395642 A GB 841811 A NL 242167 A US 3050379 A	    21-08-62
GB 911491 A		NONE	
US 3541723 A	24-11-70	AU 233765 A BE 571921 A CH 376714 A DE 1144971 B FR 1230463 A GB 866610 A IT 597932 A NL 111819 C NL 112127 C US 3074787 A US 3416901 A	    15-09-60    22-01-63 17-12-68
DE 1745911 A	14-01-71	NONE	
US 5522906 A	04-06-96	JP 7003276 A JP 7026276 A	06-01-95 27-01-95

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 97/03591

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5522906 A		JP 7157779 A	20-06-95
		JP 7145391 A	06-06-95
US 4828733 A	09-05-89	NONE	